




SCREEN is a collection of technical lighting for the outdoors. The entire collection is made of aluminium and transparent polycarbonate, has a shock resistance of IK10 and has IP65 which gives it high protection against rain and solid bodies. This post lamp is perfect for lighting gardens or parks. The 360° option allows symmetrical lighting. With a colour temperature of 3000K, this down light allows you to create warm and comfortable environments.



General characteristics

| | |
|----------|-------------|
| Fixation | Post, Floor |
| Type | I |
| IP | 65 |
| voltage | 100V-240V |
| Hertz | 50/60Hz |
| Power | 14W |
| IK | 10 |


Material

| | |
|----------------|--------------|
| Body/Structure | Aluminium+PC |
| Diffuser | PC |

Finish

| | |
|----------------|-------------|
| Body/Structure | Dark Grey |
| Diffuser | Transparent |

Lighting characteristics

| | |
|---------------------------|---|
| Light source included | Yes |
| Temperature | 3000K |
| |  |
| MacAdam Steps | 2 SDCM |
| LM | 712lm |
| CRI | >95 |
| LED lifetime | L90 B10 89000h |
| Dimmable light source | NO |
| Degrees of light aperture | 360° |
| Light direction | Accent lighting |
| Energy classification | E |

Driver

| | |
|----------------------------|----------|
| Requires Driver | Yes |
| Driver embedded | Yes |
| Power factor | 0.95 |
| Maximum driver information | 350mA CC |

File download

| | |
|-------------------|-------------------------------|
| General documents | Download > |
| Images | Download > |

2D / 3D

Download >

Download >

BIM

Download >