




LED recessed lamp for garden and terrace lighting. This 2W LED floor - recessed lamp is ideal for creating guide lights which highlight the paths in gardens and building areas. This luminaire features IP67 that gives high protection against rain and solids. It has included a honeycomb panel which improve the antiglare. It comes with IK08 shock resistance. Permits vehicle passage up to 1000Kg. With a heat temperature of 2700 K, this downlight allows warm, comfortable atmospheres to be created.



General characteristics

Fixation	Floor
Type	III
IP	67
included battery	.
Flush box	Yes
Flush box dimensions	ø32mm
Power	2W
IK	08
Cutting size	ø32mm

Material

Body/Structure	Stainless steel 316L+Aluminium
Diffuser	Glass

Finish

Body/Structure	Satin Aluminium
Diffuser	Transparent

Lighting characteristics

Light source included	Yes
Temperature	2700K
MacAdam Steps	3 SDCM
CRI	>90
LED lifetime	LM80
Degrees of light aperture	15°
Weight supported	1000Kg
Light direction	Accent lighting
Energy classification	E

Driver

Requires Driver	Yes
Driver embedded	No
Maximum driver information	700mA CC

File download

General documents	Download >
Images	Download >
2D / 3D	Download >
	Download >
BIM	Download >

